


MLVS2220P50192



外观&形状



Unit:mm	2220	
L	5.70±0.40	
W	5.20±0.40	
T	3.0max.	4.0 max.
C	1.4 max.	

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

規格

長(公釐)	5.7
寬(公釐)	5.2
高(公釐)	3.0 / 4.0 Max.
尺寸代碼 英吋(公釐)	2220 (5650)
工作電壓(V)	50
工作電壓(V)	65
崩潰電壓(V)	73.8
崩潰電壓(V)	90.2
箝制電壓(A)	10
箝制電壓(V)	135
電容(KHZ)	1
電容(pF)	-
電容(pF)	1900
電容(pF)	-
突波電流(A)	800
暫態能量(Joul)	-

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

特点

VRMS – Maximum AC operating voltage the varistor can maintain and not exceed 10 μ A leakage current

VDC – Maximum DC operating voltage the varistor can maintain and not exceed 10 μ A leakage current

VV – Voltage across the device measured at 1mA DC current. Equivalent to Vb, "Breakdown Voltage".

Vc – Maximum peak voltage across the varistor measured at 8/20 μ s waveform and 1A pulse current

Cp – Device capacitance measured with zero volt bias 1Vrms at 1MHz.

imax – Maximum peak current which may be applied with 8/20 μ s waveform without device failure

Wmax – Maximum energy that may be dissipated with the 10/1000 μ s waveform without device failure

包装讯息

包装尺寸(Inch)	载带	标准包装(KPCS)	单重(gram)	湿敏等级
13	Plastic type	1.5	0.3211	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技网站下载，若规格变更及停产，请於訂購時確認，恕不另行通知。

2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。