



AIP1040MB-1R0M



外观&形状



Series	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
AIP0840MB	8.8±0.4	8.2±0.3	3.8±0.2	1.4±0.3	5.0±0.3
AIP1030MB	11.5max.	10.0±0.3	2.8±0.2	2.0±0.5	3.0±0.5
AIP1040MB	11.5max.	10.0±0.3	3.8±0.2	2.0±0.5	3.0±0.5
AIP1050MB	11.5max.	10.0±0.3	4.8±0.2	2.0±0.5	3.0±0.5

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

 规格

長(公釐)	11.5 max.
寬(公釐)	10.0±0.3
高(公釐)	3.8±0.2
尺寸代碼 英吋(公釐)	1040
感值(uH)	1
典型值直流阻抗(mΩ)	2.85
最大值直流阻抗(mΩ)	3.3
典型值飽和電流(A)	29
最大飽和電流(A)	26
典型值溫升電流(A)	19
最大溫升電流(A)	17
耐壓(VDC)	40VDC
操作溫度(°C)	– 55 °C to + 125 °C.

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

特点

Note 1: Customized design is available, please contact us.

Note 2: All test referenced to 25°C ambient

Note 3: Inductance tolerance +/- 20%

Note 4: Inductance is measured with with LCR meters WK6500B(Wayne Kerr) or equivalent.at 100KHz/1V.

Note 5: DC resistance is measured with HIOKI® micro-ohm meter RM3543 or equivalent.

Note 6: Isat means that DC current will cause a 30% inductance reduction from initial value.

Note 7: Irms means that DC current will cause coil temp. rising to 40°C whichever is smaller.

Note 8: Withstand voltage is 40V DC.

包装讯息

包装尺寸(Inch)	標準包裝(KPCS)	單重(gram)	濕敏等級
13	0.5	2.25	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。

2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。