



# WCI1608CPR15\_



## Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

Unit:mm

| Series    | M1       | M2        | M3        | M4       | M5       | M6       |
|-----------|----------|-----------|-----------|----------|----------|----------|
| WCI1608CP | 1.8 MAX. | 1.02 MAX. | 1.12 MAX. | 0.28±0.1 | 0.96±0.1 | 0.76±0.1 |

注意 NOTICE: All Specifications are subject to change without notice.
 

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                   |                               |
|-------------------------------------------------------------------|-------------------------------|
| L size(mm)                                                        | 1.8(Max)                      |
| W size(mm)                                                        | 1.12(Max)                     |
| T size(mm)                                                        | 1.02(Max)                     |
| Size code inch (mm)                                               | 0603/1608                     |
| Inductance(nH)                                                    | 150                           |
| Tolerance                                                         | G( $\pm 2\%$ ),J( $\pm 5\%$ ) |
| Test Frequency(MHz)                                               | 150                           |
| DCR( $\Omega$ ) Max.                                              | 0.92                          |
| I <sub>rms</sub> (mA) Max.                                        | 280                           |
| Q Value (Min.)                                                    | 28                            |
| SRF[MHz]Min.                                                      | 990                           |
| Operating Temperature range(including self-temperature rising) °C | -25~+125                      |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- 1.1. Ceramic core wire wound construction.
- 1.2. Excellent inductance accuracy.
- 1.3. Inductance values from 1.6 to 470 nH.
- 1.4. Exceptional Q and high SRF special for high frequency applications.

## Packing

| Packing Reel(Inch) | Carrier Tape | Standard package quantity(KPCS) | Piece weight(gram) | MSL Level |
|--------------------|--------------|---------------------------------|--------------------|-----------|
| 7                  | Plastic type | 4                               | 0.00344            | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。