



WFI1608FNR47_



Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

Series	M1	M2	M3	M4	M5	M6
WFI1608FN	1.80 MAX.	1.20 MAX.	1.30 MAX.	0.35±0.1	0.85±0.1	0.9±0.1

注意 NOTICE: All Specifications are subject to change without notice.
 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	1.80(Max)
W size(mm)	1.3(Max)
T size(mm)	1.2(Max)
Size code inch (mm)	0603/1608
Inductance(nH)	470
Tolerance	J(±5%)
Test Frequency(MHz)	10
DCR(Ω) Max.	0.45
Irms(mA) Max.	500
SRF[MHz]Min.	555
OperatingTemperature range(including self-temperature rising) °C	-25~+125

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- 1.1. Ferrite core wire wound construction.
- 1.2. High Reliability due to wire wound type construction.
- 1.3. Inductance values from 4.9 to 650 nH.
- 1.4. Application for NFC circuit.

Packing

Packing Reel(Inch)	Carrier Tape	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level
7	Plastic type	4	0.005932	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。