



# WFI1608FT2R7\_



## Appearance & Shape



INPAQ TECHNOLOGY CO., LTD. Unit:mm

| Series    | M1        | M2        | M3        | M4        | M5        | M6        |
|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| WFI1608FT | 1.65±0.15 | 1.05±0.15 | 1.15±0.15 | 0.35±0.10 | 0.85±0.10 | 0.90±0.10 |

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| L size(mm)                                                        | 1.65±0.15 |
| W size(mm)                                                        | 1.15±0.15 |
| T size(mm)                                                        | 1.05±0.15 |
| Size code inch (mm)                                               | 0603/1608 |
| Inductance(uH)                                                    | 2.7       |
| Tolerance                                                         | K(±10%)   |
| Test Frequency(MHz)                                               | 7.9       |
| DCR(Ω) Max.                                                       | 1.5       |
| Irms(mA) Max.                                                     | 480       |
| Q Value (Min.)                                                    | 17        |
| SRF[MHz]Min.                                                      | 90        |
| Operating Temperature range(including self-temperature rising) °C | -40~+125  |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- 1.1. Ferrite core wire wound construction.
- 1.2. High Reliability due to wire wound type construction.
- 1.3. Inductance values from 0.047 to 10  $\mu$ H.
- 1.4. Application for DC power line.

## Packing

| Packing Reel(Inch) | Carrier Tape | Standard package quantity(KPCS) | Piece weight(gram) | MSL Level |
|--------------------|--------------|---------------------------------|--------------------|-----------|
| 7                  | Plastic type | 4                               | 0.005932           | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。