



MHC1608S121NZZ




Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.



INPAQ TECHNOLOGY CO., LTD.



| | |
|---|-----------|
| L | 1.60±0.15 |
| W | 0.80±0.15 |
| T | 0.80±0.15 |
| E | 0.30±0.20 |

(unit:mm)




注意 NOTICE: All Specifications are subject to change without notice.

Page 1/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

| | |
|---|------------|
| L size(mm) | 1.6±0.15 |
| W size(mm) | 0.8±0.15 |
| T size(mm) | 0.8±0.15 |
| Size code Inch(mm) | 0603(1608) |
| Impedance(Ω) | 120 |
| Tolerance(%) | ±25 |
| Test Frequency(MHz) | 100 |
| DCR(Ω) Max. | 0.05 |
| I _{rms} (mA) @85°C (Max.) | 2000 |
| I _{rms} (mA) @125°C (Max.) | 1000 |
| Operating Temperature range(including self-temperature rising) °C | -55~+125 |



注意 NOTICE: All Specifications are subject to change without notice.

Page 2/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- Combination of high frequency noise suppression with capability of handing high current
- The current rating up to 6 Amps with low DCR
- Compliant with AEC Q200

Packing



| Packing Reel(Inch) | Packaging type | Standard package quantity(PCS) | Piece weight(gram) | MSL Level |
|--------------------|----------------|--------------------------------|--------------------|-----------|
| 7 | Paper type | 4000 | 0.0051 | 1 |

注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Page 3/4

Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。