

AIP0630GX-100MPA



₲ Appearance & Shape





Series	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
AIP0530GX-MPA	5.7±0.3	5.4±0.3	3.0max.	2.1±0.2	1.5±0.3
AIP0630GX-MPA	7.1±0.4	6.5±0.3	3.0max.	3.0±0.2	2.0±0.4



注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載,若規格變更及停產,請於訂購時確認,恕不另行通知。

2. 本文件僅說明參考標準規格,如需訂購,請依實際核准所需規格進行申辦。

URL: www.inpaq.com.tw ; www.inpaqgp.com TEL:+886-37-585-55 EMAIL:info@inpaq.com.tw Updated 2023/10/13

Page 1/5

G Specification

L size(mm)	7.1±0.4
W size(mm)	6.5±0.3
T size(mm)	3.0 max.
Size codelnch (mm)	0630
Inductance(uH)	10
DCR(mΩ) Typ.	53
DCR(mΩ) Max.	62
Isat(A) Typ.	6.5
Isat(A) Max.	6
Irms(A) Typ.	4.9
Irms(A) Max.	4.7
Q Value (Typ.)	30
SRF[MHz] Typ.	13.7
Withstandvoltage(VDC)	30VDC
OperatingTemperaturerange(includingself- temperaturerising) °C	-40°C to +125°C

注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載,若規格變更及停產,請於訂購時確認,恕不另行通知。

2. 本文件僅說明參考標準規格,如需訂購,請依實際核准所需規格進行申辦。



URL: www.inpaq.com.tw ; www.inpaqgp.com TEL:+886-37-585-55 EMAIL:info@inpaq.com.tw Updated 2023/10/13

Page 2/5

G Notices

Note 1: Customized design is available, please contact us.

佳邦科技股份有限公司

Note 2: All test referenced to 25°C ambient

- Note 3: Inductance tolerance +/- 20%
- Note 4: Inductance is measured with with LCR meters WK6500B(Wayne Kerr) or equivalent.at 1MHz/1V.

Note 5: DC resistance is measured with HIOKI® micro-ohm meter RM3543 or equivalent.

Note 6: lsat means that DC current will cause a 30% inductance reduction from initial value.

Note 7: Irms means that DC current will cause coil temp. rising to 40°C whichever is smaller.

Note 8: Withstand voltage is 30V DC.

Packing

PackingReel(Inch)	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level			
13	1	0.804	1			
Por SGHNOLOGY CO., LTD ALL PS						

注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載,若規格變更及停產,請於訂購時確認,恕不另行通知。

2. 本文件僅說明參考標準規格,如需訂購,請依實際核准所需規格進行申辦。



URL: www.inpaq.com.tw ; www.inpaggp.com TEL:+886-37-585-55 EMAIL:info@inpaq.com.tw Updated 2023/10/13

Page 3/5

G Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載,若規格變更及停產,請於訂購時確認,恕不另行通知。

2. 本文件僅說明參考標準規格,如需訂購,請依實際核准所需規格進行申辦。

PSA 佳邦科技

URL: www.inpaq.com.tw ; www.inpaggp.com TEL:+886-37-585-55 EMAIL:info@inpaq.com.tw Updated 2023/10/13

Page 4/5



注意 NOTICE: All Specifications are subject to change without notice.

1. 本文件由 INPAQ 佳邦科技網站下載,若規格變更及停產,請於訂購時確認,恕不另行通知。

2. 本文件僅說明參考標準規格,如需訂購,請依實際核准所需規格進行申辦。

URL: www.inpaq.com.tw ; www.inpaqgp.com TEL:+886-37-585-55 EMAIL:info@inpaq.com.tw Updated 2023/10/13

Page 5/5