



WCI2520CPR22_



Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

Series	M1	M2		M3	M4	M5	M6
		5N6-R91	2.02 MAX.				
WCI2520CP	2.92 MAX.	1R0-150	2.10 MAX.	2.79 MAX.	0.50±0.1	1.43±0.1	2.00±0.1

Unit:mm

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/5

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	2.92(Max)
W size(mm)	2.79(Max)
T size(mm)	2.02(Max)
Size code inch (mm)	1008/2520
Inductance(nH)	220
Tolerance	G($\pm 2\%$),J($\pm 5\%$),K($\pm 10\%$)
Test Frequency(MHz)	25
DCR(Ω) Max.	0.84
I _{rms} (mA) Max.	500
Q Value (Min.)	45
SRF[MHz]Min.	700
Operating Temperature range(including self-temperature rising) °C	-25~+125

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/5

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- 1.1. Ceramic core wire wound construction.
- 1.2. Wide range of inductance can be selected.
- 1.3. Inductance values from 10 to 15000 nH.
- 1.4. Exceptional Q and high SRF special for high frequency applications.

Packing


Packing Reel(Inch)	Carrier Tape	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level
7	Plastic type	2	0.0308	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/5

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。


Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

Page 4/5

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。



注意 NOTICE: All Specifications are subject to change without notice.

Page 5/5

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。