



# WCI2012CPR24\_



## Appearance & Shape



| Series    | M1        | M2        | M3        | M4      | M5       | M6       |
|-----------|-----------|-----------|-----------|---------|----------|----------|
| WCI2012CP | 2.29 MAX. | 1.52 MAX. | 1.73 MAX. | 0.5±0.1 | 1.03±0.1 | 1.27±0.1 |

Unit:mm

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                   |                                               |
|-------------------------------------------------------------------|-----------------------------------------------|
| L size(mm)                                                        | 2.29(Max)                                     |
| W size(mm)                                                        | 1.73(Max)                                     |
| T size(mm)                                                        | 1.52(Max)                                     |
| Size code inch (mm)                                               | 0805/2012                                     |
| Inductance(nH)                                                    | 240                                           |
| Tolerance                                                         | G( $\pm 2\%$ ),J( $\pm 5\%$ ),K( $\pm 10\%$ ) |
| Test Frequency(MHz)                                               | 100                                           |
| DCR( $\Omega$ ) Max.                                              | 1                                             |
| I <sub>rms</sub> (mA) Max.                                        | 350                                           |
| Q Value (Min.)                                                    | 44                                            |
| SRF[MHz]Min.                                                      | 690                                           |
| Operating Temperature range(including self-temperature rising) °C | -25~+125                                      |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- 1.1. Ceramic core wire wound construction.
- 1.2. Excellent inductance accuracy.
- 1.3. Inductance values from 2.2 to 1000 nH.
- 1.4. Exceptional Q and high SRF special for high frequency applications.

## Packing

| Packing Reel(Inch) | Carrier Tape | Standard package quantity(KPCS) | Piece weight(gram) | MSL Level |
|--------------------|--------------|---------------------------------|--------------------|-----------|
| 7                  | Plastic type | 3                               | 0.0105             | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。