



LQA0807A6N9_



Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

Series	M1	M2	M3
LQA0807A6N9□	1.295±0.102	1.829±0.254	1.524±0.254
LQA0807A10N□	1.626±0.152	1.829±0.254	1.524±0.254
LQA0807A11N□	1.549±0.152	1.829±0.254	1.524±0.254
LQA0807A14N□	1.930±0.152	1.829±0.254	1.524±0.254
LQA0807A17N□	2.286±0.152	1.829±0.254	1.524±0.254
LQA0807A22N□	2.591±0.152	1.829±0.254	1.524±0.254

Unit:mm

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	1.295±0.102
W size(mm)	1.829±0.254
T size(mm)	1.524±0.254
Inductance(nH)	6.9
Tolerance	G(±2%),J(±5%)
Test Frequency(MHz)	400
DCR(mΩ) Max.	6
Irms(A) Max.	2.7
Q Value (Min.)	100
SRF[MHz]Min.	4600
OperatingTemperature range(including self-temperature rising) °C	-40~+125

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- 1.1. Inductance values from 6.9 nH to 22.0 nH.
- 1.2. Exceptionally high Q – up to 100.
- 1.3. Ultra-miniature, yet handles up to 2.7 Amps current.
- 1.4. Flat top and bottom for reliable pick and place and mechanical stability.
- 1.5. High reliability tests comply with AEC-Q200.

Packing

Packing Reel(Inch)	Carrier Tape	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level
7	Plastic type	2	0.014	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。