



MPA25203R3MBE




Appearance & Shape

INPAQ TECHNOLOGY CO., LTD.



INPAQ TECHNOLOGY CO., LTD.



L	2.50±0.20
W	2.00±0.20
T	0.90±0.10
E	0.50±0.30

(unit:mm)

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	2.5±0.20
W size(mm)	2.0±0.20
T size(mm)	0.9±0.10
Size code Inch(mm)	1008(2520)
Inductance(uH)	3.3
Tolerance(%)	±20
Test Frequency(MHz)	1
DCR(Ω)	0.1
Tolerance(%)	±25
SRF(MHz)Min.	30
Irms(mA)Max.	1200
Operating Temperature range(including self- temperature rising) °C	-40~+85

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- The monolithic construction performs high reliability and ensures a closed magnetic flux in a component avoids magnetic leakage and interference .
- Allow for higher mounting density.
- Low DC resistance.
- Compliant with AEC Q200

Packing

Packing Reel(Inch)	Packaging type	Standard package quantity(PCS)	Piece weight(gram)	MSL Level
7	Plastic type	3000	0.0223	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。

2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。