


# CSME0628D-6R8M



## Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

| Unit:mm |      |      |      |      |      |      |
|---------|------|------|------|------|------|------|
| ITEM    | M1   | M2   | M3   | M4   | M5   | M6   |
| DIM.    | 6.00 | 6.00 | 2.80 | 4.90 | 1.55 | 2.90 |
| TOL.    | ±0.3 | ±0.3 | MAX. | ±0.3 | ±0.3 | ±0.3 |


注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                |                 |
|----------------------------------------------------------------|-----------------|
| L size(mm)                                                     | 6.0±0.3         |
| W size(mm)                                                     | 6.0±0.3         |
| T size(mm)                                                     | 2.8 Max.        |
| Size codeinch (mm)                                             | 0628            |
| Inductance(uH)                                                 | 6.8±20%         |
| DCR(mΩ) Max.                                                   | 56              |
| Isat(A) Max.                                                   | 2.6             |
| Irms(A) Max.                                                   | 2.4             |
| Operating Temperaturerange(includingself-temperaturerising) °C | -40°C to +125°C |



注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- High saturation current realized by material properties and structure design.
- Low DC resistance to achieve high conversion efficiency and lower temperature rising.
- Low Profile: 6.0 mm × 6.0 mm × 2.8 mm.
- Magnetically shielded structure to accomplish high resolution in EMC protection.
- Halogen free, Lead Free, RoHS Compliance.
- Surface marking : None.
- The moisture sensitivity level (MSL) of products is level 1.

## Packing

| PackingReel(Inch) | Standard package quantity(KPCS) | Piece weight(gram) | MSL Level |
|-------------------|---------------------------------|--------------------|-----------|
| 13                | 2                               | 0.372              | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。

2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。