




# MCB2012S152JHP



## Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.



|   |           |
|---|-----------|
| L | 2.00±0.20 |
| W | 1.25±0.20 |
| T | 0.90±0.20 |
| E | 0.50±0.30 |

(unit:mm)

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                   |            |
|-------------------------------------------------------------------|------------|
| L size(mm)                                                        | 2.0±0.20   |
| W size(mm)                                                        | 1.25±0.20  |
| T size(mm)                                                        | 0.9±0.20   |
| Size code Inch(mm)                                                | 0805(2012) |
| Impedance(Ω)                                                      | 1500       |
| Tolerance(%)                                                      | ±25        |
| Test Frequency(MHz)                                               | 100        |
| DCR(Ω) Max.                                                       | 0.35       |
| I <sub>rms</sub> (mA) @85°C (Max.)                                | 700        |
| Operating Temperature range(including self-temperature rising) °C | -55~+125   |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- Monolithic inorganic material construction
- Closed magnetic circuit avoids crosstalk
- SMD Type & suitable for reflow and wave soldering
- Available in various sizes
- Excellent solderability and heat resistance
- High reliability
- Effectively filtering capability over a wide range of frequency
- Compliant with AEC Q200

## Packing


| Packing Reel(Inch) | Packaging type | Standard package quantity(PCS) | Piece weight(gram) | MSL Level |
|--------------------|----------------|--------------------------------|--------------------|-----------|
| 7                  | Paper type     | 4000                           | 0.0086             | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

Page 4/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。