


# SMAJ13A-AM



## Appearance & Shape



注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                      |                |
|----------------------|----------------|
| L size(mm)           | 5.22           |
| W size(mm)           | 2.76           |
| T size(mm)           | 2.26           |
| Size code(Inch (mm)) | SMA / DO-214AC |
| Direction Bi/Uni     | Uni Direction  |
| Channel              | 1              |
| VRWM (V) Max         | 13             |
| VB(V) Typical        | 14.4           |
| VB(V) Max            | 15.9           |
| Ipp (A)              | 18.6           |
| Ppp (W)              | 400            |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

Glass passivated chip junction

Reliable low cost construction utilizing molded plastic technique

Excellent clamping voltage capability

Fast response time

## Packing

| Packing Reel (Inch) | Carrier tape | Standard package quantity (KPCS) | Piece weight (gram) | MSL Level |
|---------------------|--------------|----------------------------------|---------------------|-----------|
| 13                  | Plastic type | 5                                | 0.0624              | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。

2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。