



# MHC1608S471LHP



## Appearance & Shape

INPAQ TECHNOLOGY CO., LTD.



INPAQ TECHNOLOGY CO., LTD.



|   |           |
|---|-----------|
| L | 1.60±0.15 |
| W | 0.80±0.15 |
| T | 0.80±0.15 |
| E | 0.30±0.20 |

(unit:mm)

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Specification

|                                                                          |            |
|--------------------------------------------------------------------------|------------|
| L size(mm)                                                               | 1.6±0.15   |
| W size(mm)                                                               | 0.8±0.15   |
| T size(mm)                                                               | 0.8±0.15   |
| Size code Inch(mm)                                                       | 0603(1608) |
| Impedance(Ω)                                                             | 470        |
| Tolerance(%)                                                             | ±25        |
| Test Frequency(MHz)                                                      | 100        |
| DCR(Ω) Max.                                                              | 0.2        |
| I <sub>rms</sub> (mA) @85°C (Max.)                                       | 1000       |
| I <sub>rms</sub> (mA) @125°C (Max.)                                      | 1000       |
| Operating<br>Temperature range(including self-<br>temperature rising) °C | -55~+125   |

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Notices

- Combination of high frequency noise suppression with capability of handing high current
- The current rating up to 6 Amps with low DCR
- Compliant with AEC Q200

## Packing


| Packing Reel(Inch) | Packaging type | Standard package quantity(PCS) | Piece weight(gram) | MSL Level |
|--------------------|----------------|--------------------------------|--------------------|-----------|
| 7                  | Paper type     | 4000                           | 0.0051             | 1         |

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

## Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

Page 4/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。