


CSME0840D-470M



Appearance & Shape



INPAQ TECHNOLOGY CO., LTD. Unit:mm

ITEM	M1	M2	M3	M4	M5	M6
DIM.	8.00	8.00	4.20	5.60	7.50	2.20
TOL.	±0.2	±0.2	MAX.			




注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	8.0±0.2
W size(mm)	8.0±0.2
T size(mm)	4.2 Max.
Size codeinch (mm)	0840
Inductance(uH)	47±20%
DCR(mΩ) Max.	176.8
Isat(A) Max.	1.9
Irms(A) Max.	1.75
Operating Temperature range(including self-temperature rising) °C	-25°C to +125°C



注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- High saturation current realized by material properties and structure design.
- Low DC resistance to achieve high conversion efficiency and lower temperature rising.
- Low Profile: 8.0 mm × 8.0 mm × 4.2 mm.
- Magnetically shielded structure to accomplish high resolution in EMC protection.
- Halogen free, Lead Free, RoHS Compliance.
- Surface marking : None.
- The moisture sensitivity level (MSL) of products is level 1.

Packing

Packing Reel(Inch)	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level
13	1	0.99	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。