



WCI2520C-R15_



Appearance & Shape



INPAQ TECHNOLOGY CO., LTD.

Series	M1	M2		M3	M4	M5	M6
		5N6-R91	2.02 MAX.				
WCI2520CP	2.92 MAX.	1R0-150	2.10 MAX.	2.79 MAX.	0.50±0.1	1.43±0.1	2.00±0.1

Unit:mm

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size	2.92 MAX
W size	2.79 Max
T size	2.02 Max
Size code Inch (mm)	1008(2520)
Inductance(nH)	150
Tolerance	G($\pm 2\%$), J($\pm 5\%$), K($\pm 10\%$)
Test Frequency(MHz)	25
DCR(Ω) Max.	0.7
Irms(mA) Max.	580
Q Value (Min.)	45
SRF[MHz]Min.	850
Operating Temperature range (including self-temperature rising) $^{\circ}\text{C}$	-25~+125

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/3

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

1. SCOPE

- 1.1. Ceramic core wire wound construction.
- 1.2. Wide range of inductance can be selected
- 1.3. Inductance values from 5.6 to 15000 nH.
- 1.4. Exceptional Q and high SRF special for high frequency applications.

Packing

Packing Reel(Inch)	Carrier Tape Plastic	Standard package quantity(KPCS)	Piece weight(gram)	MSL Level
7	1	2	0.0308	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/3

- 1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
- 2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。