



MHC3216S391NBE



Appearance & Shape



L	3.20±0.20
W	1.60±0.20
T	1.10±0.20
E	0.50±0.30

(unit:mm)

注意 NOTICE: All Specifications are subject to change without notice.

Page 1/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Specification

L size(mm)	3.2±0.20
W size(mm)	1.6±0.20
T size(mm)	1.1±0.20
Size code Inch(mm)	1206(3216)
Impedance(Ω)	390
Tolerance(%)	±25
Test Frequency(MHz)	100
DCR(Ω) Max.	0.09
Irms(mA) @85°C (Max.)	2000
Operating Temperature range(including self- temperature rising) °C	-55~+125

注意 NOTICE: All Specifications are subject to change without notice.

Page 2/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Notices

- Combination of high frequency noise suppression with capability of handing high current
- The current rating up to 6 Amps with low DCR

Packing


Packing Reel(Inch)	Packaging type	Standard package quantity(PCS)	Piece weight(gram)	MSL Level
7	Plastic type	3000	0.0263	1

注意 NOTICE: All Specifications are subject to change without notice.

Page 3/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。

Characteristic curve



注意 NOTICE: All Specifications are subject to change without notice.

Page 4/4

1. 本文件由 INPAQ 佳邦科技網站下載，若規格變更及停產，請於訂購時確認，恕不另行通知。
2. 本文件僅說明參考標準規格，如需訂購，請依實際核准所需規格進行申辦。